



GORILLA® Air & Multipurpose Hose

APPLICATION: A premium-quality, multipurpose industrial hose with a wide range of applications in factories, construction, agriculture, quarries, mines, railroads, the oil and gas industry, and shipbuilding. All sizes are rated at 500 psi (3.4 MPa) maximum working pressure. Nonconductive, minimum electrical resistance greater than one (1) megaohm per inch of hose length at 1000 Volts DC.

CONSTRUCTION TUBE: Nitrile synthetic rubber, RMA Class A (High Oil Resistance)

COVER: Yellow Carbryn™ synthetic rubber, RMA Class A (High Oil Resistance) MSHA approved

REINFORCEMENT: Spiral Flexten® yarn, 2" is braided synthetic yarn

TEMPERATURE: -20 °F to 190 °F (-29 °C to 88 °C)

COUPLINGS: Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

BRANDING: Example: Gorilla® 1" (25.4 mm) 500 psi. Made in USA Continental Contitech. Flame Resistant USMSHA No. 2G-14C/14.

<u>Item #</u>	<u>I.D.</u>	<u>Nom. O.D.</u>	<u>Length</u>	<u>Color</u>	<u>Max. Working Pressure</u>	<u>Weight</u>
20129568	3/8 in 9.50 mm	0.730 in 18.60 mm	100.000 ft	YELLOW	500.0 psi 3.45 MPa	0.220 lb/ft 0.33 kg/m
20129583	3/4 in 19.10 mm	1.190 in 30.20 mm	100.000 ft	YELLOW	500.0 psi 3.45 MPa	0.410 lb/ft 0.61 kg/m
20305356	2 in 50.80 mm	2.620 in 66.60 mm	50.000 ft	YELLOW	500.0 psi 3.45 MPa	1.220 lb/ft 1.82 kg/m
20026301	3/4 in 19.10 mm	1.190 in 30.20 mm	100.000 ft	YELLOW	500.0 psi 3.45 MPa	0.410 lb/ft 0.61 kg/m
20316129	3/4 in 19.10 mm	1.190 in 30.20 mm	50.000 ft	YELLOW	500.0 psi 3.45 MPa	0.410 lb/ft 0.61 kg/m