





**The Lynx bottom-loading coupler** is truly better in every way. With thousands of units now deployed around the world, in some of the most demanding terminal environments, the Lynx has earned this high praise. Performance, Durability, Ease of Maintenance. Turn to the proven performer, Lynx.



Learn more at opw-es.com/lynx.



opw-es.com

sales@mcgillhose.com

ENGINEERING | WHAT'S NEXT

## www.mcgillhose.com

East Longmeadow, MA 413-525-3977 Woburn, MA 781-933-3300 East Providence, RI 401-438-0639



## EASY TO USE, EASY TO MAINTAIN, WITH A WARRANTY THAT MAKES IT EASY TO LOVE.



## Max Surge Pressure of 500 psi

ORDERING		SPECIFICATIONS	
LYNX852VG	Long Handle, Viton <sup>®</sup> GFLT	Max Working Pressure:	80 psi
LYNX852B	Long Handle, Nitrile/Buna	Test Pressure:	120 psi
LYNX852F	Long Handle, Fluorosilicone	Max Surge Pressure:	500 psi
		Operating Temp:	-40°F to 176°

Operating Temp:	-40°F to 176°F (-40°C to 80°C)*	
Design Standard:	API RP 1004 8th Edition	
Weight:	19 lbs.	

\*Operating temp. rating will vary based on seal selection

## Our Locations:

41 Benton Dr, East Longmeadow, MA 413-525-3977 35 Industrial Pkwy Unit F, Woburn, MA 781-933-3300

920 Broadway, East Providence, RI 401-438-0639