McGill HOSE & COUPLING

HOSE STORAGE SOLUTIONS

OSHA says reduce your trips and falls

"There are many situations that may cause slips, trips and falls. The controls needed to prevent these hazards are usually obvious, but too often ignored, such as...coiling up extension cords, lines and hoses when not in use and keeping electrical and other wires out of the way." OSHA's "Fall Prevention Tips" include, "Practice good housekeeping. Keep cords, welding leads and air hoses out of walkways or adjacent work areas."

Source: www.osha.gov

Worker health and safety

OSHA's top cited workplace violation from 2013-2018 was fall protection. Falls are among the most common causes of serious work related injuries and deaths. OSHA requires employers to provide working conditions that are free of known dangers. Also, floors in work areas must be in a clean and, so far as possible, a dry condition.

Source: www.osha.gov

Why use Reelcraft?

- ✓ **Most complete product line** - We manufacture over twenty five hundred models of hose, cord and cable reels.
- ✓ **Industry leader for quality, service and delivery** - Our product quality starts with modern engineering techniques, superior manufacturing processes, and the best customer support.
- ✓ **Two year limited warranty** - We offer a two-year limited warranty on all reels manufactured by Reelcraft.
- ✓ **Easy to use interactive catalog** - Self-select the product you need based on your specific application.

REELCRAFT®

General Industrial Spring Driven Reels - Series RT

- The industrial-grade drive spring is protected in a polypropylene spool.
- Steel guide arm and base; guide arm adjusts to seven positions
- Declutching arbor eliminates reverse spring winding and torsion style latch spring is virtually unbreakable.
- Available in medium and high pressure.

RC MODEL	I.D.	FT.	PSI	LBS.	L x W x H (in)
RT450-OLP	1/4"	50	300	24	16 1/4 x 5 3/4 x 17 7/8
RT635-OLP	3/8"	35	300	21	16 1/4 x 5 3/4 x 17 7/8
RT650-OLP	3/8"	50	300	27	16 1/4 x 6 1/4 x 17 7/8
RT835-OLP	1/2"	35	300	27	16 1/4 x 6 1/4 x 17 7/8
RT850-OLP	1/2"	50	300	37	16 1/4 x 7 3/4 x 17 7/8

Hose included on all models listed.

Premium Industrial Spring Driven Reels - Series 4000 / 5000 / 5005

- Robotically welded steel base offers maximum strength and consistent quality.
- Latch cam is designed for reliable quiet operation.
- Steel components are powder coated for maximum corrosion resistance.
- Available in medium and high pressure.

RC MODEL	I.D.	FT.	PSI	LBS.	L x W x H (in)
4425 OLP	1/4"	25	300	19	12 5/8 x 5 5/8 x 12 7/8
5450 OLP	1/4"	50	300	26	14 1/4 x 6 1/8 x 14 3/8
4625 OLP	3/8"	25	300	20	12 5/8 x 5 5/8 x 12 7/8
5650 OLP	3/8"	50	300	36	16 3/4 x 5 7/8 x 17 5/8
A5825 OLP	3/8"	50	300	27	14 1/4 x 6 1/8 x 14 3/8
A5850 OLP	1/2"	35	300	41	16 3/4 x 7 1/4 x 17 5/8

Hose included on all models listed.

Heavy Duty Industrial Spring Driven Reels - Series 7000 / HD70000

- The steel guide arm and base are stamped with ribs and gussets to insure maximum strength. Guide arm adjusts to seven positions.
- Individually powder coated components offer the maximum protection from premature corrosion.
- The hose is plumbed into the base to eliminate the risk of undue stress on the swivel.

RC MODEL	I.D.	FT.	PSI	LBS.	L x W x H (in)
7650 OLP	3/8"	50	300	43	19 3/4 x 7 x 20 1/4
HD76100 OLP	3/8"	100	300	75	19 3/4 x 8 1/4 x 20 1/4
7850 OLP	1/2"	50	300	47	19 3/4 x 7 x 20 1/4
HD78075 OLP	1/2"	75	300	73	19 3/4 x 8 1/4 x 20 1/4
7650 OMP	3/8"	50	2600	55	19 3/4 x 7 x 20 1/4
7850 OMP	1/2"	50	3000	57	19 3/4 x 7 x 20 1/4
7450 OHP	1/4"	50	5000	55	19 3/4 x 7 x 20 1/4
7650 OHP	3/8"	50	4800	60	19 3/4 x 7 x 20 1/4

Hose included on all models listed.

Stainless Steel Spring Driven Reels - Series 5000 / LC / 7000

- Base and guide arm made of heavy-gauge stainless steel stampings with reinforcing ribs.
- Designed for stationary indoor and outdoor use.
- High quality stainless steel components for maximum corrosion resistance.

RC MODEL	I.D.	FT.	PSI	LBS.	L x W x H (in)
5600 OLS	3/8"	35	500	22	14 1/4 x 6 1/8 x 14 3/8
LC607 OLS	3/8"	70	300	35	19 3/8 x 8 1/4 x 20 1/2
LC800 OLS	1/2"	50	300	33	19 3/8 x 8 1/4 x 20 1/2
7800 OLS	1/2"	50	500	41	19 3/4 x 7 x 20 1/4
7800 OMS	1/2"	50	3000	43	19 3/4 x 7 x 20 1/4

Hose not included on all models listed.

Tool Balancers - Series TB / TBL

- Balances the weight of assembly tools, making them nearly weightless.
- Increases productivity by keeping tools positioned for immediate use with minimal operator motion.
- Reduces tool damage by preventing tools from being accidentally dropped.
- Reduces operator fatigue and improves safety and ergonomics.
- Safety tool clip and cable stop included.

RC MODEL	MIN - MAX LOAD (lbs)	CABLE LENGTH (ft)	LBS.	RATCHET LOCK
TB 05	3 - 5	6	1.5	NO
TB 12	8 - 12	8	10	NO
TB 15	10 - 15	8	10	NO
TB 23	16 - 23	8	10	NO
TBL 12	8 - 12	8	10	YES
TBL 15	10 - 15	8	10	YES
TBL 23	16 - 23	8	10	YES

Heavy Duty Power and Light Cord Reels - Series L 4000 / L 70000

- The robotically welded steel base offers maximum strength and consistent quality.
- A robust collector ring assures maximum conductivity current flow.
- All models are UL listed and CSA approved.
- Only the highest quality spring steel is used and conditioned to insure there are no imperfections for maximum service life.
- Declutching arbor virtually eliminates possibility of spring damage due to reverse winding.
- For indoor, non-weather tight applications only.

RC MODEL	ACCESSORY	AWG / COND.	FT.	AMPS	LBS.
L 4050 163 3	Single receptacle	16 / 3	50	13	26
L 4545 123 3	Single receptacle	12 / 3	45	15	27
L 70100 123 3	Single receptacle	12 / 3	100	15	74
L 4545 123 3A	Single receptacle	12 / 3	45	20	28
L 70100 123 3A	Single receptacle	12 / 3	100	20	74
L 4545 123 7	Duplex GFCI	12 / 3	45	15	29
L 70100 123 7	Duplex GFCI	12 / 3	100	15	76
L 70100 123 7A	Duplex GFCI	12 / 3	100	20	76
L 4545 123 9	Triple Tap	12 / 3	45	15	28
L 4050 163 1	Incandescent	16 / 3	50	10	27
L 4050 163 10	LED	16 / 3	50	13	28

Heavy Duty Welding Hose Reels - Series TW

- Double-sealed, special molded O-rings prevent leakage.
- The seals and hoses are T-grade for use with a variety of welding gases.
- The swivel inlets are both permanently identified with machined grooves on the gas side to assure proper installation.

RC MODEL	I.D.	FT.	PSI	LBS.	L x W x H (in)
TW5425 OLPT	1/4"	25	200	26	12 5/8 x 6 x 14 3/8
TW7450 OLPT	1/4"	50	200	50	19 3/4 x 7 3/8 x 20 1/4
TW84100 OLPT	1/4"	100	200	101	24 x 12 1/4 x 25 3/8
TW86075 OLPT	3/8"	75	200	99	24 x 12 1/4 x 25 3/8

Hose included on all models listed.

Models listed with an icon can ship same day upon request when the order is received by 1:00 PM Eastern Time for quantities of 10 or fewer.

IN Indiana CA California QS Indiana & California